



**ATT-ET-4.0**



TECHNICAL SPECS	STANDARD	METRIC
MAX. WORKING PRESSURE	10,500 PSI	724 BAR
LENGTH	24,00 IN	609.6 MM
WIDTH	15,50 IN	393,7 MM
HEIGHT	14,50 IN	368,3 MM
WEIGHT	104,00 LBS	47,2 KG
MOTOR	3,5 HP LEESON ENCLOSED FAN COOLED	
VOLTAGE	220 VOLT	
MINIMUM RUN WATTS	5,000	
MINIMUM START WATTS	7,500	
MAXIMUM AMP DRAW / RPM	17 AMPS / 3,450 RPM	
HYDRAULIC PUMP	2 STAGE RADIAL PISTON OVER PISTON	
TOOL OPERATION	2 TOOL SIMULTANEOUS OPERATION	

TECHNICAL SPECS	STANDARD	METRIC
RESERVOIR CAPACITY	0,90 US GALLON	3,4 LITER
CERTIFIED TO NFPA 1936-2020	YES	
<b>SIMULTANEOUS MODE</b>	<b>STANDARD</b>	<b>METRIC</b>
1ST STAGE SETTING	3,200 PSI	220 BAR
1ST STAGE FLOW	245 CU IN/MIN	4,014.8 CC/MIN
2ND STAGE SETTING	10,500 PSI	724 BAR
2ND STAGE FLOW	85 CU IN/MIN	1,392.9 CC/MIN
<b>ALTERNATING ACCELERATION MODE (PER TOOL)</b>	<b>STANDARD</b>	<b>METRIC</b>
1ST STAGE SETTING	3,200 PSI	220 BAR
1ST STAGE FLOW	490 CU IN/MIN	8,029.6 CC/MIN
2ND STAGE SETTING	10,500 PSI	724 BAR
2ND STAGE FLOW	170 CU IN/MIN	2,785.8 CC/MIN

TNT RESCUE SYSTEMS INC.  
 2490 west Oak Street  
 Ashippun, WI 53003  
[www.TNTRESCUE.com](http://www.TNTRESCUE.com)

