



# STORM SURGE

## ES100-32-18V-20V

LENGTH	37.17 IN	944.16 MM
HEIGHT	11.15 IN	283.09 MM
WIDTH	13.58 IN	344.93 MM
WEIGHT		
EXCL. BATTERY	49.45 LBS	22.43 KG
BATTERY WEIGHT:		
MILWAUKEE M18-9AH:	2.4 LBS	1.08 KG
DEWALT 20/60V-9AH:	3.4 LBS	1.54 KG
MAKITA 18V LXT-6AH	1.5 LBS	0.68 KG
MAX. SPREAD DISTANCE	31.50 IN	700.10 MM
MAX. SPREAD FORCE RANGE	50,592- 201,420 LBF	225- 895 KN
MAX. PULL DISTANCE	22.25 IN	565.15 MM
MAX. PULL FORCE	9,339 LBF	41.54 KN
POWER SOURCE OPTION	MILWAUKEE M18	
CERTIFIED TO NFPA 1936-2020	YES	
IP RATING	54	



TNT hydraulic rescue tools can be used by emergency rescue personnel during vehicle accidents, as well as in other rescue scenarios such as confined spaces, structural collapses, and forcible entry situations. These tools include cutters, spreaders, combination tools, and rams, and are available in gas, battery, and air-driven versions. More information about use and capabilities can be obtained from your local distributor.

