



## MANUFACTURERS OPERATIONAL GUIDELINE FOR OPERATING STORM 2 BATTERY POWERED TOOLS

- 1) Ensure batteries are charged with the approved enclosed Milwaukee charger.  
(NOTE: WHEN OPERATING THE STORM 2 WITH BOTH BATTERIES, THE LOWEST BATTERY WILL EQUALIZE AND MATCH THE OPPOSITE SIDE. ONLY USE 5 AMP/HR BATTERIES)
- 2) Prior to use inspect components (body, arms, blades, handle, and battery receiver)
- 3) Insert batteries into receiver located on both sides of the tool body.  
(NOTE: Both batteries are not required to operate the tool, normal operation will occur with 1 battery)
- 4) Activate the tool by pressing the on/off switch located at the rear of the tool, if switch is illuminated the tool is ready for use.
- 5) Place both hands on the tool at the desired location (red handle and twist grip at the rear of the tool)
- 6) Activate movement of the tool by twisting the handle open or close.
- 7) TNT Rescue Systems Inc. recommends not stalling any battery tool at peak maximum pressure in the open or closed position for more than 5 seconds.
- 8) If the cut or spread operation is not successful after five seconds reposition the tool and repeat the maneuver.
- 9) After use do not store any tool in the completely opened or closed position and ensure that the on/off switch is in the off position.
- 10) Inspect and clean the tool.
- 11) Recharge the batteries.
- 12) Ensure the tool is wiped dry after the exposure to inclement weather (rain snow etc.)

**\* As with any powered extrication equipment, always wear proper PPE and do not position any body parts between the tool and the vehicle.**

