



TNT hydraulic rescue tools can be used by emergency rescue personnel during vehicle accidents, as well as in other rescue scenarios such as confined spaces, structural collapses, and forcible entry situations. These tools include cutters, spreaders, combination tools, and rams, and are available in gas, battery, and air-driven versions. More information about use and capabilities can be obtained from your local distributor.

**E  
S  
1  
0  
0  
Z  
R**

<b>LENGTH</b>	34.80 IN	883.99 MM
<b>HEIGHT</b>	11.15 IN	283.09 MM
<b>WIDTH</b>	13.58 IN	344.93 MM
<b>WEIGHT</b>		
<b>EXCL. BATTERY</b>	48.20 LBS	21.86 KG
<b>BATTERY WEIGHT:</b>		
MILWAUKEE M18-9AH:	2.4 LBS	1.08 KG
DEWALT 20/60V-9AH:	3.4 LBS	1.54 KG
MAKITA 18V LXT-6AH	1.5 LBS	0.68 KG
<b>MAX. SPREAD DISTANCE</b>	27.50 IN	698.50 MM
<b>MAX. SPREAD FORCE RANGE</b>	56,128 - 228,126 LBF	249 - 1,014 KN
<b>MAX. PULL DISTANCE</b>	18.25 IN	463.55 MM
<b>MAX. PULL FORCE</b>	11,168 LBF	49.67 KN
<b>POWER SOURCE OPTION</b>	MILWAUKEE M18 / DEWALT 20V MAKITA 18V	
<b>CERTIFIED TO NFPA 1960-2024</b>	YES	
<b>IP RATING</b>	54	

