



TNT hydraulic rescue tools can be used by emergency rescue personnel during vehicle accidents, as well as in other rescue scenarios such as confined spaces, structural collapses, and forcible entry situations. These tools include cutters, spreaders, combination tools, and rams, and are available in gas, battery, and air-driven versions. More information about use and capabilities can be obtained from your local distributor.



ESLC29

LENGTH	32.99 IN	837.90 MM
HEIGHT	11.69 IN	296.83 MM
WIDTH	10.5 IN	266.70 MM
WEIGHT		
EXCL. BATTERY	51.40 LBS	23.31 KG
BATTERY WEIGHT:		
MILWAUKEE M18-9AH:	2.4 LBS	1.08 KG
DEWALT 20/60V-9AH:	3.4 LBS	1.54 KG
MAKITA 18V LXT-6AH	1.5 LBS	0.68 KG
MAX. BLADE OPENING	8.00 IN	203.00 MM
MAX. CUT REACH	5.08 IN	129.15 MM
POWER SOURCE OPTION	MILWAUKEE M18 / DEWALT 20V / MAKITA 18V	
CERTIFIED TO NFPA 1960-2024	YES	
NFPA CUT TEST	A8, B9, C9, D9, E9, F5	
IP RATING	54	

