



TNT hydraulic rescue tools can be used by emergency rescue personnel during vehicle accidents, as well as in other rescue scenarios such as confined spaces, structural collapses, and forcible entry situations. These tools include cutters, spreaders, combination tools, and rams, and are available in gas, battery, and air-driven versions. More information about use and capabilities can be obtained from your local distributor.

**ETLS40**

<b>CLOSED LENGTH</b>	21.50 IN	546.10 MM
<b>EXTENDED LENGTH</b>	42.25 IN	1073.15 MM
<b>HEIGHT</b>	10.75 IN	273.00 MM
<b>WIDTH</b>	8.10 IN	205.70 MM
<b>WEIGHT</b>		
<b>EXCL. BATTERY</b>	38.75 LBS	17.57 KG
<b>BATTERY WEIGHT:</b>		
MILWAUKEE M18-9AH:	2.4 LBS	1.08 KG
DEWALT 20/60V-9AH:	3.4 LBS	1.54 KG
MAKITA 18V LXT-6AH	1.5 LBS	0.68 KG
<b>1<sup>ST</sup> STAGE STROKE</b>	12.95 IN	329.00 MM
<b>1<sup>ST</sup> STAGE MAX. PUSH FORCE</b>	38.067 LBF	169.33 KN
<b>2<sup>ND</sup> STAGE STROKE</b>	8.70 IN	221.00 MM
<b>2<sup>ND</sup> STAGE MAX. PUSH FORCE</b>	13.088 LBF	58.21 KN
<b>POWER SOURCE OPTION</b>	MILWAUKEE M18 / DEWALT 20V / MAKITA 18V	
<b>CERTIFIED TO NFPA 1960-2024</b>	YES	
<b>IP RATING</b>	54	

