



TNT hydraulic rescue tools can be used by emergency rescue personnel during vehicle accidents, as well as in other rescue scenarios such as confined spaces, structural collapses, and forcible entry situations. These tools include cutters, spreaders, combination tools, and rams, and are available in gas, battery, and air-driven versions. More information about use and capabilities can be obtained from your local distributor.

LENGTH	31.12 IN	790.57 MM
HEIGHT	11.74 IN	298.13 MM
WIDTH	10.50 IN	266.70 MM
WEIGHT		
EXCL. BATTERY	39.8 LBS	18.05 KG
BATTERY WEIGHT:		
MILWAUKEE M18-9AH:	2.4 LBS	1.08 KG
DEWALT 20/60V-9AH:	3.4 LBS	1.54 KG
MAKITA 18V LXT-6AH	1.5 LBS	0.68 KG
MAX. BLADE OPENING	9.12 IN	231.77 MM
MAX. CUT REACH	3 IN	76.20 MM
NFPA CUT RATING	A6/B5/C7/D7/E6	
MAX. SPREAD DISTANCE	12 IN	304.8 MM
MAX. SPREAD FORCE	11,880 LBF	5,288 KN
POWER SOURCE OPTION	MILWAUKEE M18, MAKITA LXT 18V AND DEWALT 20V	
IP RATING	54	



**E
S
L
E
C
T
R
I
C**

**M
O
D
E
L**