ES100Z4

BUILT TO RESCUE

MADE IN THE USA TNT RESCUE

TNT hydraulic rescue tools can be used by emergency rescue personnel during vehicle accidents, as well as in other rescue scenarios such as confined spaces, structural collapses, and forcible entry situations. These tools include cutters, spreaders, combination tools, and rams, and are available in gas, battery, and air-driven versions. More information about use and capabilities can be obtained from your local distributor.

LENGTH	32.43 IN	823.72 MM
HEIGHT	11.15 IN	283.21 MM
WIDTH	13.58 IN	344.93 MM
WEIGHT		
EXCL. BATTERY	46.85 LBS	21.25 KG
BATTERY WEIGHT:		
MILWAUKEE M18-9AH:	2.4 LBS	1.08 KG
DEWALT 20/60V-9AH:	3.4 LBS	1.54 KG
MAKITA 18V LXT-6AH	1.5 LBS	0.68 KG
MAX. SPREAD DISTANCE	23.50 IN	596.9 MM
MAX. SPREAD FORCE RANGE	64,476 - 242,368 LBF	286 - 1,078 KN
MAX. PULL DISTANCE	14.25 IN	361.95 MM
MAX. PULL FORCE	14,368 LBF	63.91 KN
POWER SOURCE OPTION	MILWAUKEE M18 / DEWALT 20V MAKITA 18V	
CERTIFIED TO NFPA 1960-2024	YES	
IP RATING	54	



MADE IN THE USA

FOREVER WARRANTY